

What is claimed is:

1. A system comprising:

an induction machine with a stator and a rotor, said stator having a plurality of phase windings;

5 an inverter having a plurality of solid-state switches with appropriate controls and having the same number of phases as said induction machine, said inverter being connected to selectively energize said windings; and

a programmable microprocessor operatively connected to
10 said inverter and including a program for controlling said inverter that includes operating said induction machine using pole phase modulation.

2. A system according to claim 1, wherein said
15 program operates to control the induction machine as a generator.

3. A system according to claim 1, wherein said
program operates to switch control of said induction
20 machine between a motoring operation mode and a generating operation mode, each of said operation modes operates said induction machine with a desired number of poles.

4. A system according to claim 2, wherein said
25 program operates to switch control of said induction

machine between a motoring operation mode and a generating operation mode, each of said operation modes operates said induction machine with a desired number of poles.

5 5. A system according to claim 1, wherein said stator is a toroidally wound stator.

10 6. A system according to claim 1, wherein said rotor is a squirrel cage rotor.

15 7. A system according to claim 1, wherein said stator is a toroidally wound stator and said rotor is a squirrel cage rotor.

20 8. A system according to claim 1, wherein said programmable microprocessor is a digital signal processor.

SUB
A2
20 9. A system according to claim 1, wherein said microprocessor further includes steps for controlling said inverter by vector control.

10. A system according to claim 1, further comprising a position sensor operatively connected to said induction machine for providing a position indication that is

indicative of a relative position of said rotor and said stator.

11. A system comprising:

5 an induction machine with a stator and a rotor, said stator having a plurality of phase windings;

a position sensor operatively connected to said induction machine for providing a position indication that is indicative of a relative position of said rotor and said stator;

an inverter having a plurality of solid-state switches with appropriate controls and having the same number of phases as said toroidal induction machine, said inverter being connected to selectively energize said windings; and

15 a programmable microprocessor operatively connected and including a program to implement vector control of said induction machine, said microprocessor also controlling said inverter so that said induction machine operates with pole phase modulation.

20

12. A system according to claim 11, wherein said program operates to switch control of said induction machine between a motoring operation mode and a generating operation mode, each of said operation modes operates said induction machine with a desired number of poles.

25

SECRET 6802260

SUB
A3

13. A system according to claim 11, wherein said stator is a toroidally wound stator and said rotor is a squirrel cage rotor.

5

14. An automotive propulsion system including a system comprising:

SUB
A4

an induction machine with a toroidally wound stator and a squirrel cage rotor, said toroidally wound stator
10 having a plurality of phase windings;
a position sensor operatively connected to said induction machine for providing a position indication that is indicative of a relative position of said rotor and said stator;
15 an inverter having a plurality of solid-state switches and a control system, said inverter having the same number of phases as said toroidal induction machine, said inverter being connected to selectively energize said windings; and
a programmable digital signal processor operatively
20 connected to said induction machine, said programmable digital signal processor including a program to implement vector control of said induction machine, said programmable digital signal processor controlling said inverter so that said induction machine operates with a predetermined number
25 of poles using pole phase modulation.